

Package: saeczi (via r-universe)

October 14, 2026

Type Package

Title Small Area Estimation for Continuous Zero Inflated Data

Version 0.2.0.9000

Maintainer Josh Yamamoto <joshuayamamoto5@gmail.com>

Description Provides functionality to fit a zero-inflated estimator for small area estimation. This estimator is a combines a linear mixed effects regression model and a logistic mixed effects regression model via a two-stage modeling approach. The estimator's mean squared error is estimated via a parametric bootstrap method. Chandra and others (2012, <[doi:10.1080/03610918.2011.598991](https://doi.org/10.1080/03610918.2011.598991)>) introduce and describe this estimator and mean squared error estimator. White and others (2024+, <[doi:10.48550/arXiv.2402.03263](https://doi.org/10.48550/arXiv.2402.03263)>) describe the applicability of this estimator to estimation of forest attributes and further assess the estimator's properties.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Imports dplyr, lme4, purrr, progressr, furrr, future, rlang, Rcpp

RoxygenNote 7.3.1

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

Depends R (>= 4.1.0)

LinkingTo Rcpp, RcppEigen

URL <https://harvard-ufds.github.io/saeczi/>

Config/pak/sysreqs cmake make

Repository <https://harvard-ufds.r-universe.dev>

Date/Publication 2025-02-07 23:00:08 UTC

RemoteUrl <https://github.com/harvard-ufds/saeczi>

RemoteRef HEAD

RemoteSha 47c4702be0cff3d6662946dbcbc1e5d4e05b917a

Contents

pop	2
saeczi	2
samp	4

Index	5
-------	---

pop	<i>FIA Population Level Auxiliary Data for Oregon</i>
-----	---

Description

FIA Population Level Auxiliary Data for Oregon

Usage

pop

Format

An object of class `data.frame` with 10060 rows and 10 columns.

saeczi	<i>Fit a zero-inflation estimator.</i>
--------	--

Description

Fit a zero-inflation estimator.

Usage

```
saeczi(  
  samp_dat,  
  pop_dat,  
  lin_formula,  
  log_formula = lin_formula,  
  domain_level,  
  B = 100L,  
  mse_est = FALSE,  
  estimand = "means",  
  parallel = FALSE,  
  transform_fun = NULL,  
  inv_transform_fun = NULL  
)
```

Arguments

samp_dat	A data.frame with domains, auxiliary variables, and the response variable of a sample
pop_dat	A data.frame with domains and auxiliary variables of a population.
lin_formula	Formula. Specification of the response and fixed effects of the linear regression model
log_formula	Formula. Specification of the response and fixed effects of the logistic regression model
domain_level	String. The column name in samp_dat and pop_dat that encodes the domain level
B	Integer. The number of bootstraps to be used in MSE estimation.
mse_est	Logical. Whether or not MSE estimation should happen.
estimand	String. Whether the estimates should be 'totals' or 'means'.
parallel	Logical. Should the MSE estimation be computed in parallel.
transform_fun	Function. Function to be applied to the response variable prior to modeling.
inv_transform_fun	Function. Inverse of transform_fun. Required if transform_fun is specified.

Value

An object of class 'zi_mod' with defined 'print()' and 'summary()' methods. The object is structured like a list and contains the following elements:

- * call: The original function call
- * res: A data.frame containing the estimates and mse estimates
- * lin_mod: The modeling object used to fit the original linear model
- * log_mod: The modeling object used to fit the original logistic model

Examples

```
data(pop)
data(samp)

lin_formula <- DRYBIO_AG_TPA_live_ADJ ~ tcc16 + elev

result <- saeczi(samp_dat = samp,
                 pop_dat = pop,
                 lin_formula = lin_formula,
                 log_formula = lin_formula,
                 domain_level = "COUNTYFIPS",
                 mse_est = FALSE)
```

`samp`*FIA sample data for Oregon*

Description

FIA sample data for Oregon

Usage

`samp`

Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 1494 rows and 11 columns.

Index

* datasets

pop, [2](#)
samp, [4](#)

pop, [2](#)

saeczi, [2](#)
samp, [4](#)